

# Free Standing Pallet Inverters

The Premier free standing pallet inverter is the simpler and less costly option where forklifts are available and ground level loading is not essential. It has a loading capacity of 2000 kgs.

It is ideal for boxed, bagged or canned goods and is versatile enough to handle everything from yogurt and biscuits to bottles of wine or cement.

There are 3 standard jaw opening sizes, however custom built sizes are available to suit your specifications, load weights and dimensions.

## Uses Include

- Load transfer from wood to plastic or other hygienic pallets
- Recovery of damaged goods or broken boards from the bottom of the stack
- Switching to and from high quality in-house pallets
- Increased flexibility in pallet use enabling transfer to rental, expendable or customer pallets for distribution




## Key Features

- Made in the UK
- 180 degree free-standing inverter
- Loading capacity up to 2000 kilos (2 tonne)
- Single clamping table
- Loaded and relocatable by forklift truck
- Simple lever controls and attached guards
- Optional push button and automated controls plus floor fixed and photo-electric guarding
- All models fitted with dual hydraulic lever controls as standard. Extended individual push button controls, semi or fully auto-sequenced systems available as an option



Code	FS1600	FS1900	FS2200
Capacity	2000kg	2000kg	2000kg
Load Table Size	1370x1220mm (WxD)	1370x1220mm (WxD)	1370x1220mm (WxD)
Jaw Opening	1.6m (Max) - 0.92m (Min)	1.9m (Max) - 1.06m (Min)	2.2m (Max) - 1.13m (Min)
Unit Weight	1700kg	1850kg	2000kg
Guard Weight	175kg	175kg	175kg
Power Supply	3ph / 400V / 15A	3ph / 400V / 15A	3ph / 400V / 20A
Motor Size	2.2kW	3.0kW	4.0kW
Operating Space	1800x1200x2200mm (WxDxH)	1800x1200x2200mm (WxDxH)	1800x1200x2200mm (WxDxH)

Code	Description	Price Each
FS1600	Free Standing Pallet Inverter (1600mm jaw opening)	\$POA
FS1900	Free Standing Pallet Inverter (1900mm jaw opening)	\$POA
FS2200	Free Standing Pallet Inverter (2200mm jaw opening)	\$POA



Lifting & Elevating Equipment